(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 19 August 2004 (19.08.2004)

PCT

(10) International Publication Number WO 2004/070895 A3

(51) International Patent Classification7:

H01S 3/11

(21) International Application Number:

PCT/US2004/002478

(22) International Filing Date: 29 January 2004 (29.01.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/444,541

3 February 2003 (03.02.2003)

- (71) Applicant (for all designated States except US): BAE SYSTEMS INFORMATION AND ELECTRONIC SYSTEMS INTEGRATION INC. [US/US]; 65 Spit Brook Road, NHQ01-719, Nashua, NH 03061 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): POMERANZ. Leonard, A. [US/US]; 9 Deer Run Road, Hollis, NH 03049 (US).
- (74) Agent: LONG, Daniel, J.; Bae Systems Information and Electronic Systems Integration Inc., 65 Spit Brook Road, NHQ01-719, Nashua, NH 03061 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM. TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (88) Date of publication of the international search report: 3 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THULIUM LASER PUMPED MID-IR SOURCE WITH BROADBANDED OUTPUT



(57) Abstract: A Thulium laser (15) is used to directly drive a ZnGeP2 optical parametric oscillator (30) with a nominal 2 µm output to generate the 3-5 micron wavelengths. In one embodiment, the ZGP OPO is configured as a linear resonator and in another embodiment the ZGP OPO is configured as a ring resonator. The ring resonator prevents optical feedback to the Thulium laser (15) and eliminates the need for an optical isolator (24). Moreover, the Thulium laser pump (15) is implemented as a Tm: YA1O3 laser in which YAIO is the host for the Thulium YAIO is particularly beneficial as it is a mechanically hard optical material allowing high thermal loading without fracture as well as natural birefringence that can minimize thermal birefringence losses. A longer wavelength transition at 1.99 microns is selected to minimize nonlinear crystal loss. More particularly, a high power, high efficiency Tm: YA1O₃ laser repetitively Q-switched at 10 kHz is used to drive a ZnGeP2 OPO. The system is run with room temperature components and achieves over 3 W at 3-5 microns with an efficiency of 5% starting from the pump diode. A two crystal resonator (40, 42) design allows tuning over multiple spectral peaks or alternately as an ultra broad spectral source.

